

STARTER



- * EN 60155 Matching.
- * Ensure optimal turning on, thus increasing performance and life of fluo tubes.
- * Insulating Class II with self-extinguishing polycarbonate cap.
- * RF noise reducing capacitor in aluminium foil.
- * AST-480 and AST-480S: guaranteed for about 15,000 cycles.
- * AST-422S: guaranteed for about 6,000 cycles.
- * Replacement suggested in case of relamping.
- * Require ambient temperature higher than 5°C.
- * VDE certification.

Item Characteristics

Code	AST-422S
Lamp Voltage	4 ÷ 22 V
Nominal Power	4 ÷ 22 W
Connection	Single connection 110÷130V, in series 220÷240V
Diameter	20 mm
Length	37 mm
Weight	6 g
Output load (W)	4 ÷ 22 W

Performance

Energy Class	
--------------	--

Tech Info

T (°C) Working environment Temp.	-25°C / +35°C
Fulfilled Directives and norms	2006/95/CE * Bassa Tensione 2012/19/UE * RAEE EN 60155 * anno 1996 (+A2:2007) 2011/65/UE * RoHS

More InfoTech

TABELLA D'IMPIEGO - TABLE OF USE - TABLA DE EMPLEJO

Collegamento Conexión 230V	Per LAMPADE LINEARI Para LÁMPARAS LINEAL - For LINEAR LAMPS								Per DURALUX L Para - For DURALUX L		
	W	W	W	W	W	W	W	W	W	W	
	4	10	15	18	22	30	38	36	58	18	36
	6	13	16	20	32	40	65	24			
AST-480S SUPER	*	*	*	*	*	*	*	*	*	*	*
AST-480 Standard	*	*	*	*	*	*	*	*	*	*	*
AST-422S Series *	*	*	*	*	*	*	*	*	*	*	*

* Anche per circuito singolo a 110-130V - Also for 110-130V single circuit - También para circuito simple a 110-130V

Shipping info

Single pack dimensions L x H x D (mm)	10 x 4 x 4
Item barcode	8011905805241
Pack	1000 pz
Master barcode	8011905751661

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products.