

## BULKHEAD T&O IP65 - Round



\* Typically used for diffused lighting for both indoor and outdoor or wet environments (IP65).

\* Substitutes ceiling fixtures with fluorescent lamps to give immediate lighting without flickering and increased duration.

\* Essential design anywhere.

\* Shockproof plastic 1004 body and screen.

\* Operating temperature: -20°C +35°C.

\* Typical uses: to light stairwells, terraces, corridors, communal areas, gardens, bathrooms and anterooms.

### Item Characteristics

Code	BH20
Lamp Voltage	220-240 V
Nominal Power	20 W
Base	cavi/wires
Lamp Current	0,09 A
Flux	2000 LUMEN
Light Tonality	Natural white
Colour temperature	4000 K
Opening beam	120°
Diameter	220 mm
Lenght	73 mm
Weight	420 g


### Performance

Axis cd	560
Photometry	F145
Irc/Ra	>80
Lifetime	25000 h
Energy Class	A+
kWh/1000h	20

### Tech Info

Dimmable	NO
Number of ON-OFF cycles	100000
Power Factor	0,9
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
Mercury (mg)	0
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C
Fulfilled Directives and norms	2006/95/CE * Bassa Tensione 2004/108/CE * Compatibilità Elettromagnetica 2011/65/UE * RoHS 2012/19/UE * RAEE EN 61547 * anno 2010 EN 55015 * anno 2014 EN 61000-3-2 * anno 2007 EN 61000-3-2/A1/A2 * anno 2011 EN 61000-3-3 * anno 2014 EN 60598-1 EN 60598-2-2 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling

### Spectroradiometry and Photometry



Eulumdat file for lighting calculations available on the website

### Shipping info

Single pack dimensions L x H x D (mm)	225 x 225 x 73
Item barcode	8011905843632
Pack	10 pz
Master barcode	8011905788919