

DURALUX S LED



- * Directly retrofit of fluorescent lamps with G23 base.
- * No need to modify the fixture already wired for fluorescents.
- * Increased safety for users thanks to the plastic body.
- * Working position: universal.
- * Working temperature: -25° +40°C.

USAGE INFORMATION

- * Do not use with dimmer.

Item Characteristics

Code	L2003
Lamp Voltage	220-240 V
Nominal Power	7 W
Base	G23
Lamp Current	0,03 A
Flux	640 LUMEN
Colour temperature	4000 K
Opening beam	360°
Diameter	33 mm
Length	164 mm
Weight	35 g

Performance

Irc/Ra	>80
Lifetime	25000 h
Energy Class	A+
kWh/1000h	7
Equivalence with incandescent lamp	51 W

Tech Info

Dimmable	NO
Open fittings	YES
Number of ON-OFF cycles	100000
Power Factor	0,87
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
Mercury (mg)	0
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C
Fulfilled Directives and norms	2009/125/EC * Ecodesign 1194/2012 * Regulation for Ecodesign 2015/1428 * Regulation for Ecodesign 2010/30/EU * Energy Labelling 874/2012 * Regulation for Energy Labelling 2011/65/EU * RoHS 2012/19/EU * RAEE 2014/30/EU * EMC (Compatibilità Elettromagnetica) 2014/35/EU * LVD (Bassa Tensione) CEI EN 55015:2014 (+A1:2016) CEI EN 60968:2016 CEI EN 61000-3-2:2015 CEI EN 61000-3-3:2014 (+EC:2014/+EC:2016) CEI EN 61547:2010 CEI EN 62031:2009 (+A1/+A2:2015) CEI EN 62471:2010 IEC/TR 62471-2:2009 CEI EN 62560:2013 (+A1:2016) CEI 34-141:2012

Shipping info

Single pack dimensions L x H x D (mm)	35 x 35 x 165
Item barcode	8011905848415
Pack	10 pz
Master barcode	8011905848422