


Lineare ERRE7s 360°



* Linear LED lamp with a 330° light emission and offset lamp caps. The particular position of the lamp caps allows these lamps to be inserted into all fixtures with R7s lampholders. Thermoconductive polymers. Explosion proof glass not necessary. Cannot be used with dimmers, except if differently specified.

Item Characteristics

Code	L2972N
Lamp Voltage	220-240 V
Nominal Power	11,5 W
Base	R7s
Lamp Current	0,09 A
Flux	1521 LUMEN
Colour temperature	4000 K
Opening beam	330°
Diameter	29 mm
Lenght	118 mm
Lenght 1	29 mm
Lenght 2	118 mm
Weight	30 g

Performance

Irc/Ra	80
Lifetime	15000 h
Energy Class	A++
kWh/1000h	12
Equivalence with incandescent lamp	100 W

Tech Info

Dimmable	NO
Open fittings	YES
Number of ON-OFF cycles	100000
Power Factor	0,55
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C
Fulfilled Directives and norms	2011/65/UE * RoHS 2012/19/UE * RAEE 2014/30/UE * Compatibilità Elettromagnetica 2014/35/UE * Bassa Tensione EN 61547 * anno 2010 EN 55015 * anno 2014 EN 61000-3 -2 * anno 2007 (+A1/+A2:2011) EN 61000-3-3 * anno 2014 EN 62471 * anno 2010 IEC/TR 62471-2 EN 62031 * anno 2009 (+A1:2013) EN 62560 * anno 2013 EN 60968 * anno 2013 244/2009 * Progettazione Eco Compatibile 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling 2009/125/CE * Progettazione Eco Compatibile 1194/2012 * Progettazione Eco Compatibile

Shipping info

Item barcode	8011905922795
Pack	10 pz