

TUBOLED GLASS LL6 - 50.000h



- * LED tubes with glass cover.
 - * Wide lighting distribution curve.
 - * Color rendering > 80.
 - * Operating voltage 220-240V.
 - * Working position: universal.
 - * Replacing 18W, 36W and 58W T8 tubes: high energy saving.
 - * Immediate switch on, no flickering or buzzes.
 - * Great flux maintenance.
- USAGE INFORMATION

- * Do not use with dimmers.
- * In case fluorescent tubes must be replaced, follow the simple assembly instructions indicated below. See instruction on the website.
- * Do not use in installations in series.
- * Package: industrial pack of 10pcs that can be sold separately.

Item Characteristics

Code	L36860LL6
Lamp Voltage	220-240 V
Nominal Power	18 W
Base	G13
Lamp Current	0,086 A
Nominal Flux	2300 LUMEN
Light Tonality	Cool white
Colour temperature	6400 K
Opening beam	300°
Diameter	28 mm
Lenght	1200 mm

Performance

Irc/Ra	>80
Lifetime	50000 h
Energy Class	A++
kWh/1000h	18

Tech Info

Dimmable	NO
Number of ON-OFF cycles	100000
Power Factor	0,96
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
Mercury (mg)	0

LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C
Fulfilled Directives and norms	2009/125/EC * Ecodesign 1194/2012 * Regulation for Ecodesign 2015/1428 * Regulation for Ecodesign 2010/30/EU * Energy Labelling 874/2012 * Regulation for Energy Labelling 2011/65/EU * RoHS 2012/19/EU * RAEE 2014/30/EU * EMC (Compatibilità Elettromagnetica) 2014/35/EU * LVD (Bassa Tensione) CEI EN 55015:2014 (+A1:2016) CEI EN 60598-1:2015 (+EC:2015/+EC:2016) CEI EN 60598-2-1:1997 CEI EN 61000-3-2:2015 CEI EN 61000-3-3:2014 (+EC:2014/+EC:2016) CEI EN 61347-1:2016 CEI EN 61347-2-13:2015 CEI EN 61547:2010 CEI EN 62031:2009 (+A1/+A2:2015) CEI EN 62471:2010 IEC/TR 62471-2:2009 CEI EN 62493:2015 CEI EN 62776:205 CEI 34-141:2014 Risk Group 0

Shipping info

Single pack dimensions L x H x D (mm)	1270 x 39 x 39
Item barcode	8011905862237
Pack	10 pz
Master barcode	8011905862244