

## Linear ERRE7s



### Item Characteristics

Code	LF1970W
Lamp Voltage	220-240 V
Nominal Power	4 W
Base	R7s
Lamp Current	0,02 A
Flux	450 LUMEN
Colour temperature	2700 K
Opening beam	320°
Diameter	14 mm
Lenght	78 mm
Lenght 1	14 mm
Lenght 2	78 mm
Weight	8 g

### Performance

Irc/Ra	80
Lifetime	10000 h
Energy Class	A++
kWh/1000h	4
Equivalence with incandescent lamp	39 W

### Tech Info

Dimmable	NO
Open fittings	YES
Number of ON-OFF cycles	100000
Power Factor	0,78
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C
Fulfilled Directives and norms	2011/65/UE * RoHS 2012/19/UE * RAEE 2014/30/UE * Compatibilità Elettromagnetica 2014/35/UE * Bassa Tensione EN 61547 * anno 2010 EN 55015 * anno 2014 EN 61000-3-2 * anno 2007 (+A1/+A2:2011) EN 61000-3-3 * anno 2014 EN 62471 * anno 2010 IEC/TR 62471-2 EN 62031 * anno 2009 (+A1:2013) EN 62560 * anno 2013 EN 60968 * anno 2013 244/2009 * Progettazione Eco Compatibile 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling 2009/125/CE * Progettazione Eco Compatibile 1194/2012 * Progettazione Eco Compatibile

### Shipping info

Item barcode	8011905930561
Pack	10 pz