

SLIMFLUX



- * Ultra flat LED appliances for direct lighting; thickness:9 mm.
- * Same flow as the 4x18W module with fluorescent tubes.
- * Side heat dissipation.
- * Possible installation: suspended or recessed mounting.
- * Immediate switch-on.
- * Maintenance-free.
- * Color tonality Natural white.
- * Extremely high color rendering: Ra>80.
- * Fuse for mains protection.
- * Working position: universal.
- * IP40.
- * White painted metal body.
- * Adjustable suspension wires kit available with separate kit, code KTLP-SPB.
- * Remote power supply included.
- * Do not use with dimmer.
- * DRIVER (included in the panel package) INFO: - Input voltage 100-240Vac - Input current 0.5A max - Frequency 50/60Hz - Power factor =0.9 - Output Voltage: 35-48Vdc - Output current 840mA ±5% - Output power 40W max - Driver dimensions: 177x54x39mm.

Item Characteristics

Code	LP30120NWB
Nominal Power	40 W
Base	cavi/wires
Lamp Current	0,19 A
Flux	3200 LUMEN
Light Tonality	Natural white
Colour temperature	4000 K
Lenght	1195 mm
Lenght 1	295 mm
Lenght 2	9 mm
Weight	3800 g

Performance

Photometry	LP30120NWB
Irc/Ra	>80
Lifetime	35000 h
Energy Class	A+

Tech Info

Dimmable	NO
Number of ON-OFF cycles	100000

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products.

Power Factor	0,90
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
Mercury (mg)	0
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C
Fulfilled Directives and norms	2006/95/CE * Bassa Tensione 2004/108/CE * Compatibilità Elettromagnetica 2011/65/UE * RoHS 2012/19/UE * RAEE EN 61547 * anno 2010 EN 55015 * anno 2014 EN 61000-3-2 * anno 2007 (+A1/+A2:2011) EN 61000-3-3 * anno 2014 EN 62471 * anno 2010 IEC/TR 62471-2 EN 62031 * anno 2009 (+A1:2013) EN 62560 * anno 2013 EN 60968 * anno 2013 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling 2009/125/CE * Progettazione Eco Compatibile 1194/2012 * Progettazione Eco Compatibile

Spectrocolorimetry and Photometry

Eulumdat file for lighting calculations available on the website

Shipping info

Item barcode	8011905850852
Pack	1 pz